

Document Name : Technical Specifications of 4 port RS485 Hub, Model SC08S4



The RS485 Hub transforms RS485 bus into star topology making RS485 a dependable network. Each RS485 Hub Port is Isolated from the other and support 1.2Km run of multidropped RS485 devices. Additionally, the Hub ports are Optically Isolated, Short Circuit, Surge & ESD protected rendering ruggedness to your network. In case if any there is a cable fault or a RS485 device failure or a shorting in the network, the problem is restricted to only that ports of the Hub. Connect with ease as many as 256

RS485 device without bothering too much about the distance, number of Multidrops and cabling hassles.

Specifications

4 Input Ports	: RS485 / RS422
1 Common Port	: RS232/485
Connectors	: Screw Type Terminal block. 5 Pin for Common & 3 Pine for Input ports
Cables	: Twisted or Shielded Twisted pair
Baud Rate	: 300 to 115 kbps. Auto Baud rate
Distance	: 0 to 1.2 Km @ 115kbps to 300 bps
Multidrops	: 64 devices per port
Auto Direction Control:	Yes. For RS485
Operating mode	: Asynchronous Half Duplex
Isolation	: 2.5 KV RMS Optical Isolation between each port
Protection	: Surge Protection upto 1500W / 8/20 μ s 3,000A lightning surge protection : RS485 Short Circuit protection. Each port Isolated from the other i.e in case of Short circuit etc in any port, other ports would keep operating safely : 15KV ESD Protection
LED Indicators	: Power, TX, RX common for all port and separate Error Led for each port
Power Supply	: Dual Power Input : 230V AC Internal SMPS, Range 100 to 240V AC and 230V AC External Adapter, 12V DC, 1A output
Power Consumption	: 1W
Dimensions	: 31 (H) x 140 (D) x 210 (W) without clamp : 31 (H) x 140 (D) x 250 (W) with clamp
Weight	: Appx. 1Kg
Working environment	: Temp -40 to 85°C : Relative humidity 5% to 95%

San Telequip (P) Ltd.,
504/505 Deron Heights, Baner Road, Baner
Pune 411045, Mah, India
Phone : +91-20-27293455, 9764027070, 8390069393
email : info@santelequip.com



Connecting. Converting. Leading !

Model Code : SC08S4 A C X

Type of Input Ports : A : RS485/422

Type of Common Port: C : RS232/485

Power Supply : X : 230V AC Built In + Provision for 230V AC external Adapter

Application Diagram

