

San Telequip (P) Ltd.,
504/505 Deron Heights, Baner Road, Baner
Pune 411045, Mah, India
Phone : +91-20-27293455, 9764027070, 8390069393
email : info@santelequip.com



Connecting. Converting. Leading !

One Channel Digital Video Optical Transmitter & Receiver, SC09VFN 1

Overview



SCV09VFN series video Digital Optical Converter adopt the advanced international digital video and optical fiber transmission technology, and implement the transmission of real-time & synchronization, no-distortion and high quality video effect. The play-and-plug design makes the installation more convenient and easier.

Features

- 10-bit digital code and non-compression type video transmission
- Support any high-resolution video signal
- 5Hz-10MHz video channel
- Automatic compatible PAL, NTSC and SECAM video system
- With APC circuit, constant input optical power, and large dynamic range
- Advanced self-adapting technology

Technical Specifications

Video

Video interface number	1 channel video
Bandwidth of video	8MHz
Video input & output impedance	75 Ω (imbalance), BNC
Video input & output voltage	1Vpp
Differential gain	DG <1% (typical value)
Differential phase	DP <0.6° (typical value)
Weighted signal-to-noise ratio	S/N \geq 67dB (Weighted)

Data

Physical interface	Screw type terminals
Interface Signal	RS485/RS422/RS232
Baud Rate	0-400Kbps
BER	< 10 ⁻⁹

Audio

Interface port	Industrial standard port
Audio input/output impedance	600 Ω (balance/imbalance)
Audio input/output voltage	2Vpp (typical value)
Audio input/output level	0 dbm (typical value)
Audio bandwidth	10Hz to 20kHz
Audio digital bandwidth	24 bit
Audio signal-to-noise ratio	S/N \geq 95Db (weighted)

Ethernet

Physical interface	RJ45
Operating mode	Full duplex / half duplex
Operating mode	Full duplex/ full-duplex
Support agreement	IEEE802.3, 10M, 10/100M Auto

San Telequip (P) Ltd.,
504/505 Deron Heights, Baner Road, Baner
Pune 411045, Mah, India
Phone : +91-20-27293455, 9764027070, 8390069393
email : info@santelequip.com



Connecting. Converting. Leading !

Phone

Physical interface	RJ11
Voice bandwidth	8kHz
Special function	Support the call display, With hands-free function
Working mode	Point to point link, SPC Exchanges method

Fiber

Connector	FC
Fiber type	Single-mode fiber, Single fiber
Transmission distance	Single mode 20Km

LED Indications

POWER, FIBER, LED (VIDEO)

Environmental

Operating temperature	-30°C to +75°C
Storage environment	-40°C to +85°C
Relative humidity	0-95% (non condensation)
Power supply voltage	AC220V, 50Hz, External Adapter
Dimensions	10.8*10.6*2.7 (cm)

Ordering Information

Model Selection: SC09VFN 1 S T AC DA A E

SC09VFN : Basic Product Code
1 : 1 Channel Video Port
M / S : M: Multimode, S: Singlemode
T/R : T: Transmitter, R: Receiver
AC : External Adapter
DA/DB : Data Port – DA: Unidirectional, DB: Bi Directional
A : Audio Port
E : Ethernet Port
Series : H Fixed. For Internal Use

Application Diagram

