

San Telequip (P) Ltd.,  
 504/505 Deron Heights, Baner Road, Baner  
 Pune 411045, Mah, India  
 Phone : +91-20-65001587, 9764027070, 8390069393  
 email :info@santelequip.com



Connecting. Converting. Leading !

**RS232 to Bluetooth Converter, Model SC10B**



- ✓ Replaces any existing RS232 cable
- ✓ Full Bluetooth 2.0+ EDR support
- ✓ It can also communicate with other Bluetooth devices
- ✓ No external software needed
- ✓ Easy to install
- ✓ Baud rate : 1200bps to 115.2kbps
- ✓ Distance from 150 to 300 feet with CLASS 2 and CLASS 1
- ✓ Enhanced Antenna
- ✓ Plug-and Play type

**Specification**

Bluetooth Interface:

Bluetooth Profiles : Generic Access Profile, Serial Port Profile  
 Bluetooth radio : Class 2 / Class 1  
 : SPP with Class1 & Class 2 support  
 : OPP / FTP with Class1 & Class 2 support ( to be added later on )

External Antennae : 2 db with SMA connector. Optional 5db

Serial interface : RS232 Female DSUB-9 Connector

Power supply : 5V DC/ 500mA.

Power connector : External adapter with DC Jack, 1.3 mm

Operating temperature : +5 to +55°C


Storage temperature : -25 to +70°C

Construction : ABS cover transparent blue

Dimensions : 110x43x20 mm

Weight : 150 grams

**Bluetooth Application Diagram**



**Ordering Code : SC10B**

SC10B : RS232 to Bluetooth Converter