



**SAN TELEQUIP**  
Connecting. Converting. Leading.

- Page 1 of 3

San Telequip (P) Ltd.,  
504 & 505 Deron Heights, Baner Road  
Pune 411045, India  
Phone : +91-20-27293455, 9764027070, 8390069393  
email : [info@santelequip.com](mailto:info@santelequip.com)

---



### Mechanical Characteristics

IP rating : IP40  
Weight : 1600g  
Installation : DIN-Rail

### Dimension

Size (W\*H\*D) : 70mm\*150 mm\*120mm

### Environment

Operating temperature : -40°C to 85°C  
Storage temperature : -40°C~85°C  
Relative humidity : 0~95% (non-condensing)

### Industrial Standards

EMI: FCC Part 15 , CISPR (EN55022) class A

EMS:

IEC(EN)61000-4-2(ESD)

IEC(EN)61000-4-3(RS)

IEC(EN)61000-4-4(EFT)

IEC(EN)61000-4-5(Surge)

IEC(EN)61000-4-6(CS)

IEC 60068-2-27(Shock)

IEC 60068-2-32(Freefall)

### Ordering Model Code : IESG S 108-4S-\*F-XX00-YY-Z-R

Model	10/100/1000 Base T Ports	1000Base FX Ports	1000 Base FX SFP Ports
IESG S 108-4S	8		4
IESG S 108-2F-XX00-YY-Z	8	2	
IESG S 108-4F-XX00-YY-Z	8	4	

**4S** : 4\*1000X SFP slots

**4F** : 4 \* 100FX Fiber Ports

**XX** : Fiber type

: MM for Multimode, SM for Singlemode. Singlemode is by default

**00** : Fiber distance. 20Km by default

**YY** : Fiber Connector

: SC for SC Connector, ST for ST Connector, FC for FC Connector

**Z** : **Input Supply** :

: DC for 12/24/48 DC ( 10.8 to 52.8V ) & AC for 110/220V AC/DC ( 88 to 264V )

: 12/24/48V DC is by default

**R** : Dual Power Supply. Single Supply is default.

San Telequip (P) Ltd.,  
504 & 505 Deron Heights, Baner Road  
Pune 411045, India  
Phone : +91-20-27293455, 9764027070, 8390069393  
email : [info@santelequip.com](mailto:info@santelequip.com)



## Dimension

