

San Telequip (P) Ltd.,
 504/505 Deron Heights, Baner Road, Baner
 Pune 411045, Mah, India
 Phone : +91-20-65001587, 9764027070, 8390069393
 email : info@santelequip.com



Connecting. Converting. Leading!

Document Name: User Manual for SC04-M2, RS 232 TO RS 485 (2 WIRE) CONVERTER.

INTRODUCTION

SMARTCONVERTER –SC04 M2 converts RS 232 signal to RS 485 2 Wire (Isolated differential level) signal. It works on 24 DC supply with Auto Baud Rate (ABRT) Feature enable upto 115kbps. LED indications for Serial transmissions & Power are provided. True 3 way 3KV Isolation is provided along with additional Surge & ESD protection on data lines.

RS232 INTERFACE DETAILS

RS 232 Connector : 9 Pin D type Female

Recommended cable connection for RS232C side

Your Serial Port		Signal	SC04-M2 SIDE
9 Pin D Type	25 Pin D Type		9 Pin D Type (Male)
1	8	DCD	1
2	3	RxD	2
3	2	TxD	3
4	20	DTR	4
5	7	GND	5
6	6	DSR	6
7	4	RTS	7
8	5	CTS	8
9	22	RI	9

Direction of RS232C signal

PIN	DIRECTION
2	OUTGOING FROM SC04
3	INCOMING FOR SC04
5	GND

RS485 INTERFACE DETAILS

RS 485 Connector : 2 Pin Screw type Howder

SIGNAL of SC04U	DIRECTION	Will Connect to
TX +	Bi-directional Signal	TX + of your device.
TX --	Bi-directional Signal	TX -- of your device.

Power Supply : 24V DC, Range 18 to 72V DC
 CONNECTOR : 3 Pin Screw type Howder

ENCLOSURE : ABS Plastic enclosure
 DIMENSIONS : 50 x 24 x 90 mm [W * H * D]
 MOUNTING : DIN Rail